

HAND DRY CUTTER 8203E THE AUTONOMOUS



Cordless metal cutting circular saw by Jepson Power for fast and burr free cutting of metal sheets, gratings, sandwich panels, etc. without coolant

- No need for lubrication thanks to our DRY CUT TECHNOLOGY
- Ideal for cutting metal sheets, gratings, sandwich panels, trapezoidal sheets, steel pipes & profiles, nonferrous metals and composite materials
- Equipped with a Ø 203/48T carbide tipped „LBS impact resistant“ saw blade for the highest cutting life and quality
- Chip collector for clean work

Scope of delivery:


- Carry case
- Ø 203 / 48T carbide tipped „LBS impact resistant“ saw blade
- 2x high performance 18V LiHD 5,5A batteries
- Air-cooled LiHD high speed loading station



ECO-FRIENDLY
with Dry Cutting-Technology



Ideal for cutting metal sheets, gratings and sandwich panels up to 67 mm



Optional: Guide rail 1.400 mm with 2 C-clamps 608275SET



Depth adjustment with scaling



Chip Collector



CAS battery-powered



Voltage	No load speed	Net weight	Blade size	Bore
18 V	3.500 min ⁻¹	5,4 kg	Ø 203 mm	Ø 25,4/20

Hand Dry Cutter 8203E case 2x batteries charger	Reference
with Ø 203 / 48T LBS saw blade impact-resistant	608295E
with Ø 203 / 48T LBS saw blade impact-resistant and guide rail set	608295ESET

Max. cutting capacities	90°		45° (bevel cut)	
	Round	67 x 6	42 x 4	
Square	67 x 67 x 6	42 x 42 x 4		
Angle	67 x 6	42 x 4		
Plane	10	8		
Cutting depth	67	42		

ACCESSORIES (OPTIONAL)

Selecting the correct number of teeth depends on the wall/diameter of the material. We will be happy to advise you. +49 (0) 2403 64 55 0

Carbide tipped saw blades	Ø [mm]	Teeth	Bore [mm]	Kerf [mm]	Max. Speed	Reference
Steel (thin-walled) "LBS - impact resistant"	203	48	25,4	1,2	3.800 min ⁻¹	72220348 
Stainless steel	203	54	25,4	1,7	3.500 min ⁻¹	72120354I 



High performance 18V LiHD 5,5A battery (CAS)
Ref. 608295EB



Air-cooled LiHD high speed loading station
Ref. 230 V 608295EC2
Ref. 110 V 608295EC1



Set of 2 adapters
Ref. 608275A



Guide rail set
Length 1.400 mm
C-clamps 2 pieces
Ref. 608275SET



Connector for additional guide rails
Ref. 608275B